HSDe – High-Speed Data Ethernet

Perfectly Assembled Cables – Our USPs

- Automated production line with transfer technology and process monitoring
- Compliance with the smallest processing tolerances
- Globally standardized machinery
- Cable cross-section 0.35 mm²



Your Advantages

- > Robust data transmission with LVDS principle
- Less mating processes due to a unit chamber concept and different housings
- > Small installation space with a robust design
- > 180° variants: 7 codings + waterproof;
- angled variants: only as door connector (without housing)

Technical Information

Electrical

Return loss

Mechanical

Keying efficiency Engagement force Retention force latch Mating cycles ≥ 80 N ≤ 30 N ≥ 110 N ≥ 25

 \geq 25 dB, DC up to 100 MHz

 \geq 15 dB, 100 MHz up to 500 MHz \geq 10 dB, 500 MHz up to 1 GHz

Environmental

Temperature range-40 °C up to +105 °CQualification according toLV 214 / USCAR

Specification according to Rosenberger datasheet

Requirements

2 data pairs for bi-directional data transmission or simultaneous voltage and data supply in a compact design for frequencies up to 1 GHz

Applications

- Cameras
- > ADS / ADAS
- Displays
- > ECU network connection

Protocols & Signals

- Automotive Ethernet
- Broad-R-Reach



MD in a Nutshell

The C.A.S.E. megatrend describes the four essential future topics for the automotive industry: Connected, Autonomous, Shared & Service and Electric. Data plays a central role and drives the future of the automotive industry. Data is generated, transferred, merged and evaluated. We are experts in the transmission of the rapidly increasing data volumes and have developed the latest technological solutions for this future topic.





Worldwide leading company for data transmission solutions in vehicles



Approx. 6,000 employees worldwide



Accredited in-house test laboratory

Do you have any questions or need a data transmission solution in vehicles? Please contact us: product-info@md-elektronik.com

www.md-elektronik.com